


Climbing frames "Superstar", electric

The "Superstar" climbing frames from Schelde Sports are available in a 3-section or 4-section design and can be used horizontally, vertically and diagonally. They are operated electrically. They are supplied with 4 floor provisions: 2 brass floor anchors for securing in a vertical position and 2 floor plates to prevent prints being made in the floor by the other wheels. For use in combination with ceiling units, boxes, combi-frames, etc. The options are endless.

- Safe, closed oval, solid steel uprights
- Solid wooden rungs
- Improved torsion stability
- Steplessly adjustable in height
- Dual safety suspension system



Climbing frame in horizontal position



Locking system and floor anchor



Solid wooden rungs

Technical data:

Uprights:	Oval shaped, solid steel 100x50 mm profile with durable epoxy coating.
Rungs:	9 round solid ash wood rungs, 35 mm, fitted securely with plastic clamping rings, rung distance 390 mm. Top rung, also the supporting beam, is made of steel with an epoxy coating.
Wheels:	smooth, 32 mm wide rubber-coated, non-marking wheels, diameter 125 mm
Dimensions:	Uprights: centre to centre 640 mm
Total width:	4-section: 267 cm 3-section: 203 cm
Height:	370 cm
Operation:	Via control panel. Wiring to be installed by third party.
Obstacle-free:	For sports halls where an obstacle-free wall section of at least 2 metres is required, 3-section or 4-section hoistable climbing frames are available.
Valid standard:	NEN-EN 12346

International

E-mail: export@scheldesports.nl
www.scheldesports-international.com

The Netherlands

E-mail: verkoop@janssen-fritsen.nl
www.janssen-fritsen.nl

Belgium

E-mail: info@janssen-fritsen.be
www.janssen-fritsen.be


Climbing frames "Superstar", electric

The climbing frames from Schelde Sports are a multifunctional and secure system:

- They can be used in various positions: diverse horizontal positions, one vertical position and a range of diagonal positions.
- Simple electric operation via built-in or wall-mounted control panel.
- All elements are finished smoothly and together with the oval and round shapes, there are no sharp edges.
- The uprights are made of solid steel, for extra strength and rigidity.
- Rungs are made of solid ash wood for increased stability
- The "Superstar" is standard fitted with a double safety suspension system

Safety

The safety of children and teachers is priority with Schelde Sports. For this reason, Schelde Sports fits all of its climbing frames standard with a safety suspension system.



Safety suspension device

Variation options

The climbing frame offers many challenging options. Moreover, in combination with other Schelde Sports systems, the climbing frame can form a significant part of a challenging exercise circuit. Combination with, for example, ceiling units, the Schelde Sports telescopic uprights, gymnastic beams and mats means the possibilities are endless.



Adjustment options

The adjustable climbing frame can be set to various positions. With the support of belts from ceiling units, you can electrically operate the horizontal frame, to set it at various heights. Each climbing frame can also be positioned vertically and secured at the base to the floor fixing. Finally, various diagonal positions are also possible and the incline can be adjusted to the child's capacity.



International

E-mail: export@scheldesports.nl
www.scheldesports-international.com

The Netherlands

E-mail: verkoop@janssen-fritsen.nl
www.janssen-fritsen.nl

Belgium

E-mail: info@janssen-fritsen.be
www.janssen-fritsen.be