

Conical floor sleeve, for horizontal bar

Ref. 1388090

The cast iron, conical floor sleeve is used to firmly secure an inserted upright for use with a traditional horizontal bar or in combination with, for example, rotating wall bars. The depth and the material used for this floor sleeve guarantee absolute stability and sturdiness. The perfect shape and fit rule out any deformation of the inserted upright. Ring and cover are indestructible and, if necessary, can be cladded by a flooring supplier. The cover is very stable and does not 'jump up' when anyone walks over it. The cover can easily be removed with a cover lifter.



Floor sleeve with ring, without cover



Floor sleeve with ring and cover

Technical data floor sleeve

Material: Sturdy cast iron, equipped with extra sturdy collar on the top. Exterior has rough finish for improved adhesion. Equipped with extra horizontal and vertical reinforcement ribs. The underside is watertight and sealed with a 3 mm support plate.

Dimensions: Interior diameter top 130 mm, wall thickness 4 mm.
Height 350 mm.
In-built depth minimum 450 mm.

Technical data ring and cover

Material: Ring made of 5 mm thick bronze. Height adjustable to accommodate any level differences in the floor; after installation.

Brass cover, 5 mm thick.
Dimensions: Ring exterior diameter 189 mm.
interior diameter 140 mm.
Cover exterior diameter 149.5 mm.

Item 1388090 floor sleeve conical with ring and cover
Item 4101710 floor sleeve conical without ring and cover

International

E-mail: export@scheldesports.nl
www.scheldesports-international.com

The Netherlands

E-mail: verkoop@janssen-fritsen.nl
www.janssen-fritsen.nl

Belgium

E-mail: info@janssen-fritsen.be
www.janssen-fritsen.be

Floor sleeve short with eye, for tensioning and anchoring

Ref. 1384120

The short floor sleeve with eye can be used to anchor and tension gym equipment, sports equipment and accessories used with ceiling units. The closed eye can be rotated 360°, allowing the floor sleeve to be used in any direction.



Installed sleeve with cladded cover



Floor sleeve 1384120. Also available without ring and cover, item 1384125 (not pictured)

Technical data floor sleeve

Material: Made of top quality, hot-dip galvanised steel. The floor sleeve incorporates a steel plate with an eye that can be rotated 360°. Completely safe anchoring via the closed eye.
Dimensions: 6 sturdy ridges on the top ensure excellent stability.
 Interior diameter 76 mm, wall thickness 5 mm.
 Height 73 mm.
 In-built depth minimum 85 mm.

Technical data ring and cover

Material: Ring made of 5 mm thick bronze. Height adjustable to accommodate any level differences in the floor, after installation.
 Brass cover, 5 mm thick.
Dimensions: Ring exterior diameter 189 mm.
 interior diameter 140 mm.
 Cover exterior diameter 149.5 mm.
Note: Tensile force per tensioning point 8,000 N.
 The cover can be cladded by the flooring supplier if necessary.

Item 1384120 floor sleeve short with eye, with ring and cover
 Item 1384125 floor sleeve short with eye, without ring and cover

International

E-mail: export@scheldesports.nl
www.scheldesports-international.com

The Netherlands

E-mail: verkoop@janssen-fritsen.nl
www.janssen-fritsen.nl

Belgium

E-mail: info@janssen-fritsen.be
www.janssen-fritsen.be