

DualTube ceiling-mounted basketball backstop

Stability and minimum post vibration are the key characteristics of the DualTube ceiling-mounted basketball backstop. The frame consists of 2 strong, vertical main round tubes which, at the top, are braced to the side. Together these form a triangle. The triangle is commonly recognised as the most stable and sturdy shape. This triangular construction hinges as a whole into position for use and is kept in position by 2 hinged bracing tubes. The backstop is controlled electronically and is extremely easy to use. Safety suspension mechanism comes standard included. Standard equipped with key-operated control box and official 180x105 cm 12 mm glass backboard with a blue, high-density foam padding. The set is completed with a Schelde Sports Pro 180° Dunk Ring, meeting FIBA requirements, and a nylon net.



LEVEL 2

Technical data:

Main unit:	Consists of 2 steel tubes Ø114.3 x 2.6 mm, braced to the side, for stability in every direction. The triangular shape creates perfect stability and cuts out just about all vibrations.
Foldaway:	Can be folded away forwards or backwards using the double, hinged braces made from a tube Ø45x2 mm. When the unit is folded away to the front it should be considered that sufficient space is required, as determined in the standard DIN7899. Models: <ul style="list-style-type: none"> • Standard foldaway forwards 6.50 to 10 m ceiling height • Standard foldaway backwards 6.50 to 10.50 m ceiling height Electronic folding mechanism using a 3Ph - 400V motor placed on the frame where the hinged braces and safety suspension device are also situated. Remote control optional.
Height adjustment:	Height can be adjusted either manually or electronically.
Finish:	All metal parts are covered with an impact-resistant powder coating RAL 9010 (white).
Safety:	Safety suspension device included. With steel cable, conform to EN360 standard.
Backboards:	105x180 cm, 12 mm tempered glass or acrylic, with cut out at ring height, in a white steel varnished frame.
Backboard padding:	Included as standard. Blue, high-density foam protective padding.
Basketball ring:	Schelde Sports Pro 180° Dunk Ring. Top competition breakaway dunk ring with multi-directional force flex and concealed net attachments. FIBA Level 1 & 2 approved
Basketball net:	Heavy duty, nylon net, white
Suspension beams:	The backstop is supplied with 3 tubes 100x60x3 L-2900, which are used for installation of the entire backstop. These tubes are to be secured to the construction by the contractor. Any additional auxiliary steel is to be provided locally by contractor.
Standards:	FIBA level 2 approved, conforming to DIN7899 and EN1270 standards.



Schelde Sports Pro 180° Dunk Ring



International

E-mail: export@scheldesports.com
www.scheldesports.com

The Netherlands

E-mail: verkoop@janssen-fritsen.nl
www.janssen-fritsen.nl

Belgium

E-mail: info@janssen-fritsen.be
www.janssen-fritsen.be